

CIS VMware vSphere 7.0 vCenter Appliance Lookup Service STIG Benchmark

v1.0.0 - 08-19-2025

Terms of Use

Please see the below link for our current terms of use:

<https://www.cisecurity.org/cis-securesuite/cis-securesuite-membership-terms-of-use/>

For information on referencing and/or citing CIS Benchmarks in 3rd party documentation (including using portions of Benchmark Recommendations) please contact CIS Legal (legalnotices@cisecurity.org) and request guidance on copyright usage.

NOTE: It is **NEVER** acceptable to host a CIS Benchmark in **ANY** format (PDF, etc.) on a 3rd party (non-CIS owned) site.

Table of Contents

Terms of Use	1
Table of Contents	2
Overview	4
Target Technology Details	4
Intended Audience.....	4
Recommendation Definitions.....	5
Title	5
Assessment Status.....	5
Automated	5
Manual.....	5
Profile	5
Description.....	5
Rationale Statement	5
Audit Procedure.....	5
Remediation Procedure.....	6
Additional Information.....	6
Profile Definitions	7
Acknowledgements	8
Recommendations	9
1 STIG RULES	9
1.1 VCLU-70-000001 (Manual).....	10
1.2 VCLU-70-000002 (Manual).....	12
1.3 VCLU-70-000003 (Manual).....	14
1.4 VCLU-70-000004 (Manual).....	16
1.5 VCLU-70-000005 (Manual).....	18
1.6 VCLU-70-000006 (Manual).....	21
1.7 VCLU-70-000007 (Manual).....	23
1.8 VCLU-70-000008 (Manual).....	25
1.9 VCLU-70-000009 (Manual).....	26
1.10 VCLU-70-000010 (Manual).....	27
1.11 VCLU-70-000011 (Manual).....	28
1.12 VCLU-70-000012 (Manual).....	30
1.13 VCLU-70-000013 (Manual).....	32
1.14 VCLU-70-000014 (Manual).....	34
1.15 VCLU-70-000015 (Manual).....	36
1.16 VCLU-70-000016 (Manual).....	38
1.17 VCLU-70-000017 (Manual).....	39
1.18 VCLU-70-000018 (Manual).....	41
1.19 VCLU-70-000019 (Manual).....	43
1.20 VCLU-70-000020 (Manual).....	45

1.21 VCLU-70-000021 (Manual).....	47
1.22 VCLU-70-000022 (Manual).....	49
1.23 VCLU-70-000023 (Manual).....	51
1.24 VCLU-70-000024 (Manual).....	53
1.25 VCLU-70-000025 (Manual).....	55
1.26 VCLU-70-000026 (Manual).....	57
1.27 VCLU-70-000027 (Manual).....	59
1.28 VCLU-70-000028 (Manual).....	61
1.29 VCLU-70-000029 (Manual).....	64
1.30 VCLU-70-000030 (Manual).....	66
1.31 VCLU-70-000031 (Manual).....	67

Appendix: Summary Table	69
--------------------------------------	-----------

Appendix: Change History	71
---------------------------------------	-----------

Overview

Target Technology Details

VMware vSphere 7.0 vCenter Appliance Lookup Service Secure Technical Implementation Guide (STIG)

Version: 1 Release: 2 Benchmark

Date: 26 Jul 2023

Intended Audience

This benchmark is intended for system and application administrators, security specialists, auditors, help desk, and platform deployment personnel who plan to develop, deploy, assess, or secure solutions that incorporate VMware vSphere 7.0 vCenter Appliance Lookup Service and are looking to comply with the STIG guidance

Recommendation Definitions

The following defines the various components included in a CIS recommendation as applicable. If any of the components are not applicable it will be noted, or the component will not be included in the recommendation.

Title

Concise description for the recommendation's intended configuration.

Assessment Status

An assessment status is included for every recommendation. The assessment status indicates whether the given recommendation can be automated or requires manual steps to implement. Both statuses are equally important and are determined and supported as defined below:

Automated

Represents recommendations for which assessment of a technical control can be fully automated and validated to a pass/fail state. Recommendations will include the necessary information to implement automation.

Manual

Represents recommendations for which assessment of a technical control cannot be fully automated and requires all or some manual steps to validate that the configured state is set as expected. The expected state can vary depending on the environment.

Profile

A collection of recommendations (or rules) for securing a technology or a supporting platform. STIG Benchmark profiles are used to identify which Vulnerability Severity Category Code (CAT) each rule is associated with.

Description

The Rule Title from the STIG.

Rationale Statement

Detailed reasoning for the recommendation to provide the user a clear and concise understanding on the importance of the recommendation.

Audit Procedure

Systematic instructions for determining if the target system complies with the recommendation.

Remediation Procedure

Systematic instructions for applying recommendations to the target system to bring it into compliance according to the recommendation.

Additional Information

Supplementary information that does not correspond to any other field but may be useful to the user.

Profile Definitions

The following configuration profiles are defined by this Benchmark:

- **SEVERITY: CAT I**

Items in this profile exhibit one or more of the following characteristics:

- are considered to be high severity
- are intended for environments or use cases where following STIG based security guidance is paramount.
- acts as defense in depth measure.
- may negatively inhibit the utility or performance of the technology.

This profile is intended for servers and workstations.

- **SEVERITY: CAT II**

Items in this profile exhibit one or more of the following characteristics:

- are considered to be medium severity
- are intended for environments or use cases where following STIG based security guidance is paramount.
- acts as defense in depth measure.
- may negatively inhibit the utility or performance of the technology.

This profile is intended for servers and workstations.

- **SEVERITY: CAT III**

Items in this profile exhibit one or more of the following characteristics:

- are considered to be low severity
- are intended for environments or use cases where following STIG based security guidance is paramount.
- acts as defense in depth measure.
- may negatively inhibit the utility or performance of the technology.

This profile is intended for servers and workstations.

Acknowledgements

The Recommendations in this Benchmark are a representation of the Rules in the unclassified DISA STIG for VMware vSphere 7.0 vCenter Appliance Lookup Service

Recommendations

1 STIG RULES

VMware vSphere 7.0

VMware vSphere 7.0 vCenter Appliance Lookup Service Secure Technical
Implementation Guide (STIG)

Version: 1 Release: 2 Benchmark

Date: 26 Jul 2023

CLASSIFICATION unclassified

1.1 VCLU-70-000001 (Manual)

Profile Applicability:

- SEVERITY: CAT II

Description:

Lookup Service must limit the amount of time that each Transport Control Protocol (TCP) connection is kept alive.

GROUP ID: V-256706 RULE ID: SV-256706r888709

Rationale:

Denial of service (DoS) is one threat against web servers. Many DoS attacks attempt to consume web server resources in such a way that no more resources are available to satisfy legitimate requests.

In Tomcat, the "connectionTimeout" attribute sets the number of milliseconds the server will wait after accepting a connection for the request Uniform Resource Identifier (URI) line to be presented. This timeout will also be used when reading the request body (if any). This prevents idle sockets that are not sending HTTP requests from consuming system resources and potentially denying new connections.

Audit:

At the command prompt, run the following command:

xmllint --xpath '/Server/Service/Connector[@port="\${bio-custom.http.port}"]/@connectionTimeout' /usr/lib/vmware-lookupsvc/conf/server.xml
--

Expected result:

connectionTimeout="60000"

If the output does not match the expected result, this is a finding.

Remediation:

Navigate to and open:

```
/usr/lib/vmware-lookupsvc/conf/server.xml
```

Configure the <Connector> node with the value:

```
connectionTimeout="60000"
```

Example:

```
<Connector .. connectionTimeout="60000" ..>
```

Restart the service with the following command:

```
# vmon-cli --restart lookupsvc
```

Additional Information:

CCI-000054 Limit the number of concurrent sessions for each organization-defined account and/or account type to an organization-defined number.

- NIST SP 800-53::AC-10
- NIST SP 800-53A::AC-10.1 (ii)
- NIST SP 800-53 Revision 4::AC-10
- NIST SP 800-53 Revision 5::AC-10

1.2 VCLU-70-000002 (Manual)

Profile Applicability:

- SEVERITY: CAT II

Description:

Lookup Service must limit the number of concurrent connections permitted.

```
GROUP ID: V-256707
RULE ID: SV-256707r888712
```

Rationale:

Resource exhaustion can occur when an unlimited number of concurrent requests are allowed on a website, facilitating a denial-of-service attack. Unless the number of requests is controlled, the web server can consume enough system resources to cause a system crash.

Mitigating this kind of attack will include limiting the number of concurrent HTTP/HTTPS requests. Each incoming request requires a thread for the duration of that request. If more simultaneous requests are received than can be handled by the currently available request processing threads, additional threads will be created up to the value of the "maxThreads" attribute.

Audit:

At the command prompt, run the following command:

```
# xmllint --xpath '/Server/Service/Connector[@port="{bio-custom.http.port}"]/maxThreads' /usr/lib/vmware-lookupsvc/conf/server.xml
```

Expected result:

XPath set is empty

If the output does not match the expected result, this is a finding.

Remediation:

Navigate to and open:

/usr/lib/vmware-lookupsvc/conf/server.xml

In the <Connector> node, remove the "maxThreads" key/value pair.

Restart the service with the following command:

```
# vmon-cli --restart lookupsvc
```

Additional Information:

CCI-000054 Limit the number of concurrent sessions for each organization-defined account and/or account type to an organization-defined number.

- NIST SP 800-53::AC-10
- NIST SP 800-53A::AC-10.1 (ii)
- NIST SP 800-53 Revision 4::AC-10
- NIST SP 800-53 Revision 5::AC-10

1.3 VCLU-70-000003 (Manual)

Profile Applicability:

- SEVERITY: CAT II

Description:

Lookup Service must limit the maximum size of a POST request.

```
GROUP ID: V-256708
RULE ID: SV-256708r888715
```

Rationale:

The "maxPostSize" value is the maximum size in bytes of the POST that will be handled by the container FORM URL parameter parsing. Limit its size to reduce exposure to a denial-of-service attack.

If "maxPostSize" is not set, the default value of 2097152 (2MB) is used. Lookup Service is configured in its shipping state to not set a value for "maxPostSize".

Audit:

At the command prompt, run the following command:

```
# xmllint --xpath '/Server/Service/Connector[@port="{bio-
custom.http.port}"]/@maxPostSize' /usr/lib/vmware-lookupsvc/conf/server.xml
```

Expected result:

XPath set is empty

If the output does not match the expected result, this is a finding.

Remediation:

Navigate to and open:

/usr/lib/vmware-lookupsvc/conf/server.xml

In the <Connector> node, remove the "maxPostSize" key/value pair.

Restart the service with the following command:

```
# vmon-cli --restart lookupsvc
```

Additional Information:

CCI-000054 Limit the number of concurrent sessions for each organization-defined account and/or account type to an organization-defined number.

- NIST SP 800-53::AC-10
- NIST SP 800-53A::AC-10.1 (ii)
- NIST SP 800-53 Revision 4::AC-10
- NIST SP 800-53 Revision 5::AC-10

1.4 VCLU-70-000004 (Manual)

Profile Applicability:

- SEVERITY: CAT II

Description:

Lookup Service must protect cookies from cross-site scripting (XSS).

```
GROUP ID: V-256709
RULE ID: SV-256709r888718
```

Rationale:

Cookies are a common way to save session state over the HTTP(S) protocol. If an attacker can compromise session data stored in a cookie, they are better able to launch an attack against the server and its applications.

When a cookie is tagged with the "HttpOnly" flag, it tells the browser that this particular cookie should only be accessed by the originating server. Any attempt to access the cookie from client script is strictly forbidden.

Satisfies: SRG-APP-000001-WSR-000002, SRG-APP-000223-WSR-000011, SRG-APP-000439-WSR-000154

Audit:

At the command prompt, run the following command:

```
# xmllint --format /usr/lib/vmware-lookupsvc/conf/context.xml | xmllint --
xpath '/Context/@useHttpOnly' -
```

Expected result:

useHttpOnly="true"

If the output does not match the expected result, this is a finding.

Remediation:

Navigate to and open:

```
/usr/lib/vmware-lookupsvc/conf/context.xml
```

Add the following configuration to the <Context> node:

```
useHttpOnly="true"
```

Example:

```
<Context useHttpOnly="true">
```

Restart the service with the following command:

```
# vmmon-cli --restart lookupsvc
```

Additional Information:

CCI-000054 Limit the number of concurrent sessions for each organization-defined account and/or account type to an organization-defined number.

- NIST SP 800-53::AC-10
- NIST SP 800-53A::AC-10.1 (ii)
- NIST SP 800-53 Revision 4::AC-10
- NIST SP 800-53 Revision 5::AC-10

CCI-001664 Recognize only session identifiers that are system-generated.

- NIST SP 800-53::SC-23 (3)
- NIST SP 800-53A::SC-23 (3).1 (ii)
- NIST SP 800-53 Revision 4::SC-23 (3)
- NIST SP 800-53 Revision 5::SC-23 (3)

CCI-002418 Protect the confidentiality and/or integrity of transmitted information.

- NIST SP 800-53 Revision 4::SC-8
- NIST SP 800-53 Revision 5::SC-8

1.5 VCLU-70-000005 (Manual)

Profile Applicability:

- SEVERITY: CAT II

Description:

Lookup Service must record user access in a format that enables monitoring of remote access.

GROUP ID: V-256710 RULE ID: SV-256710r888721

Rationale:

Remote access can be exploited by an attacker to compromise the server. By recording all remote access activities, it will be possible to determine the attacker's location, intent, and degree of success.

Tomcat can be configured with an "AccessLogValve", a component that can be inserted into the request processing pipeline to provide robust access logging. The "AccessLogValve" creates log files in the same format as those created by standard web servers. When "AccessLogValve" is properly configured, log files will contain all the forensic information necessary in the case of a security incident.

Satisfies: SRG-APP-000016-WSR-000005, SRG-APP-000093-WSR-000053, SRG-APP-000095-WSR-000056, SRG-APP-000096-WSR-000057, SRG-APP-000097-WSR-000058, SRG-APP-000098-WSR-000059, SRG-APP-000098-WSR-000060, SRG-APP-000099-WSR-000061, SRG-APP-000100-WSR-000064, SRG-APP-000375-WSR-000171, SRG-APP-000374-WSR-000172

Audit:

At the command prompt, run the following command:

<pre># xmllint --xpath '/Server/Service/Engine/Host/Valve[@className="org.apache.catalina.valves.AccessLogValve"]/@pattern' /usr/lib/vmware-lookupsvc/conf/server.xml</pre>

Expected result:

pattern="%t %l [RemoteIP] %{X-Forwarded-For}i %u [Request] %h:%{remote}p to local
%{local}p - %H %m %U%q [Response] %s - %b bytes [Perf] process %Dms / commit
%Fms / conn [%X]"

If the output does not match the expected result, this is a finding.

Remediation:

Navigate to and open:

/usr/lib/vmware-lookupsvc/conf/server.xml

Inside the <Host> node, find the "AccessLogValve" <Valve> node and replace the "pattern" element as follows:

```
pattern="%t %l [RemoteIP] %{X-Forwarded-For}i %u [Request] %h:%{remote}p to local  
%{local}p - %H %m %U%q [Response] %s - %b bytes [Perf] process %Dms / commit  
%Fms / conn [%X]"
```

Restart the service with the following command:

```
# vmon-cli --restart lookupsvc
```

Additional Information:

CCI-000067 Employ automated mechanisms to monitor remote access methods.

- NIST SP 800-53::AC-17 (1)
- NIST SP 800-53A::AC-17 (1).1
- NIST SP 800-53 Revision 4::AC-17 (1)
- NIST SP 800-53 Revision 5::AC-17 (1)

CCI-000130 Ensure that audit records contain information that establishes what type of event occurred.

- NIST SP 800-53::AU-3
- NIST SP 800-53A::AU-3.1
- NIST SP 800-53 Revision 4::AU-3
- NIST SP 800-53 Revision 5::AU-3 a

CCI-000131 Ensure that audit records containing information that establishes when the event occurred.

- NIST SP 800-53::AU-3
- NIST SP 800-53A::AU-3.1
- NIST SP 800-53 Revision 4::AU-3
- NIST SP 800-53 Revision 5::AU-3 b

CCI-000132 Ensure that audit records containing information that establishes where the event occurred.

- NIST SP 800-53::AU-3
- NIST SP 800-53A::AU-3.1
- NIST SP 800-53 Revision 4::AU-3
- NIST SP 800-53 Revision 5::AU-3 c

CCI-000133 Ensure that audit records containing information that establishes the source of the event.

- NIST SP 800-53::AU-3
- NIST SP 800-53A::AU-3.1
- NIST SP 800-53 Revision 4::AU-3
- NIST SP 800-53 Revision 5::AU-3 d

CCI-000134 Ensure that audit records containing information that establishes the outcome of the event.

- NIST SP 800-53::AU-3
- NIST SP 800-53A::AU-3.1
- NIST SP 800-53 Revision 4::AU-3
- NIST SP 800-53 Revision 5::AU-3 e

CCI-001462 The information system provides the capability for authorized users to capture/record and log content related to a user session.

- NIST SP 800-53::AU-14 a
- NIST SP 800-53A::AU-14.1 (i)
- NIST SP 800-53 Revision 4::AU-14 (2)

CCI-001487 Ensure that audit records containing information that establishes the identity of any individuals, subjects, or objects/entities associated with the event.

- NIST SP 800-53::AU-3
- NIST SP 800-53A::AU-3.1
- NIST SP 800-53 Revision 4::AU-3
- NIST SP 800-53 Revision 5::AU-3 f

CCI-001889 Record time stamps for audit records that meet organization-defined granularity of time measurement.

- NIST SP 800-53 Revision 4::AU-8 b
- NIST SP 800-53 Revision 5::AU-8 b

CCI-001890 Record time stamps for audit records that use Coordinated Universal Time, have a fixed local time offset from Coordinated Universal Time, or that include the local time offset as part of the time stamp.

- NIST SP 800-53 Revision 4::AU-8 b
- NIST SP 800-53 Revision 5::AU-8 b

1.6 VCLU-70-000006 (Manual)

Profile Applicability:

- SEVERITY: CAT II

Description:

Lookup Service must generate log records for system startup and shutdown.

```
GROUP ID: V-256711
RULE ID: SV-256711r888724
```

Rationale:

Logging must be started as soon as possible when a service starts and when a service is stopped. Many forms of suspicious actions can be detected by analyzing logs for unexpected service starts and stops. Also, by starting to log immediately after a service starts, it becomes more difficult for suspicious activity to go unlogged.

On the vCenter Server Appliance (VCSA), the "vmware-vmon" service starts up the Java virtual machines (JVMs) for various vCenter processes, including Lookup Service, and the individual json configuration files control the early JVM logging. Ensuring these json files are configured correctly enables early Java "stdout" and "stderr" logging.

Satisfies: SRG-APP-000089-WSR-000047, SRG-APP-000092-WSR-000055

Audit:

At the command prompt, run the following command:

```
# grep StreamRedirectFile /etc/vmware/vmware-vmon/svcCfgfiles/lookupsvc.json
```

Expected result:

"StreamRedirectFile":

"%VMWARE_LOG_DIR%/vmware/lookupsvc/lookupsvc_stream.log",

If no log file is specified for the "StreamRedirectFile" setting, this is a finding.

Remediation:

Navigate to and open:

/etc/vmware/vmware-vmon/svcCfgfiles/lookupsvc.json

Below the last line of the "PreStartCommandArg" block, add or reconfigure the following line:

"StreamRedirectFile":

"%VMWARE_LOG_DIR%/vmware/lookupsvc/lookupsvc_stream.log",

Restart the appliance for changes to take effect.

Additional Information:

CCI-000169 Provide audit record generation capability for the event types the system is capable of auditing as defined in AU-2 a on organization-defined information system components.

- NIST SP 800-53::AU-12 a
- NIST SP 800-53A::AU-12.1 (ii)
- NIST SP 800-53 Revision 4::AU-12 a
- NIST SP 800-53 Revision 5::AU-12 a

CCI-001464 Initiates session audits automatically at system start-up.

- NIST SP 800-53::AU-14 (1)
- NIST SP 800-53A::AU-14 (1).1
- NIST SP 800-53 Revision 4::AU-14 (1)
- NIST SP 800-53 Revision 5::AU-14 (1)

1.7 VCLU-70-000007 (Manual)

Profile Applicability:

- SEVERITY: CAT II

Description:

Lookup Service log files must only be accessible by privileged users.

```
GROUP ID: V-256712
RULE ID: SV-256712r918958
```

Rationale:

Log data is essential in the investigation of events. If log data were to become compromised, competent forensic analysis and discovery of the true source of potentially malicious system activity would be difficult, if not impossible, to achieve.

In addition, access to log records provides information an attacker could use to their advantage because each event record might contain communication ports, protocols, services, trust relationships, usernames, etc. The Lookup Service restricts all access to log files by default, but this configuration must be verified.

Satisfies: SRG-APP-000118-WSR-000068, SRG-APP-000119-WSR-000069, SRG-APP-000120-WSR-000070

Audit:

At the command prompt, run the following command:

```
# find /var/log/vmware/lookupsvc -xdev -type f ! -name lookupsvc-init.log -a
'(' -perm -o+w -o -not -user lookupsvc -o -not -group lookupsvc ')' -exec ls
-l {} \;
```

If any files are returned, this is a finding.

Note: Prior to Update 3h, the user and group should be root.

Remediation:

At the command prompt, run the following commands:

```
# chmod o-w /var/log/vmware/lookupsvc/<file>
# chown lookupsvc:lookupsvc /var/log/vmware/lookupsvc/<file>
```

Note: Substitute with the listed file.

Additional Information:

CCI-000162 Protect audit information from unauthorized access.

- NIST SP 800-53::AU-9
- NIST SP 800-53A::AU-9.1
- NIST SP 800-53 Revision 4::AU-9
- NIST SP 800-53 Revision 5::AU-9 a

CCI-000163 Protect audit information from unauthorized modification.

- NIST SP 800-53::AU-9
- NIST SP 800-53A::AU-9.1
- NIST SP 800-53 Revision 4::AU-9
- NIST SP 800-53 Revision 5::AU-9 a

CCI-000164 Protect audit information from unauthorized deletion.

- NIST SP 800-53::AU-9
- NIST SP 800-53A::AU-9.1
- NIST SP 800-53 Revision 4::AU-9
- NIST SP 800-53 Revision 5::AU-9 a

1.8 VCLU-70-000008 (Manual)

Profile Applicability:

- SEVERITY: CAT II

Description:

Lookup Service application files must be verified for their integrity.

```
GROUP ID: V-256713  
RULE ID: SV-256713r888730
```

Rationale:

Verifying the Lookup Service application code is unchanged from its shipping state is essential for file validation and nonrepudiation of the Lookup Service. There is no reason the MD5 hash of the RPM original files should be changed after installation, excluding configuration files.

Audit:

At the command prompt, run the following command:

```
# rpm -V vmware-lookupsvc | grep "^..5....." | grep -E "\.war|\.jar|\.sh|\.py"
```

If there is any output, this is a finding.

Remediation:

Reinstall the vCenter Server Appliance (VCSA) or roll back to a backup. VMware does not support modifying the Lookup Service installation files manually.

Additional Information:

CCI-001749 The information system prevents the installation of organization-defined software components without verification the software component has been digitally signed using a certificate that is recognized and approved by the organization.

- NIST SP 800-53 Revision 4::CM-5 (3)

1.9 VCLU-70-000009 (Manual)

Profile Applicability:

- SEVERITY: CAT II

Description:

Lookup Service must only run one webapp.

```
GROUP ID: V-256714  
RULE ID: SV-256714r888733
```

Rationale:

VMware ships Lookup Service on the vCenter Server Appliance (VCSA) with one webapp. Any other path is potentially malicious and must be removed.

Audit:

At the command prompt, run the following command:

```
# ls -A /usr/lib/vmware-lookupsvc/webapps/*.war
```

Expected result:

/usr/lib/vmware-lookupsvc/webapps/ROOT.war

If the output does not match the expected result, this is a finding.

Remediation:

For each unexpected directory returned in the check, run the following command:

```
# rm /usr/lib/vmware-lookupsvc/webapps/<NAME>
```

Restart the service with the following command:

```
# vmon-cli --restart lookupsvc
```

Additional Information:

CCI-001749 The information system prevents the installation of organization-defined software components without verification the software component has been digitally signed using a certificate that is recognized and approved by the organization.

- NIST SP 800-53 Revision 4::CM-5 (3)

1.10 VCLU-70-000010 (Manual)

Profile Applicability:

- SEVERITY: CAT II

Description:

Lookup Service must not be configured with the "UserDatabaseRealm" enabled.

```
GROUP ID: V-256715  
RULE ID: SV-256715r888736
```

Rationale:

The Lookup Service performs user authentication at the application level and not through Tomcat. By default, there is no configuration for the "UserDatabaseRealm" Tomcat authentication mechanism. As part of eliminating unnecessary features and to ensure the Lookup Service remains in its shipping state, the lack of a "UserDatabaseRealm" configuration must be confirmed.

Audit:

At the command prompt, run the following command:

```
# grep UserDatabaseRealm /usr/lib/vmware-lookupsvc/conf/server.xml
```

If the command produces any output, this is a finding.

Remediation:

Navigate to and open:

```
/usr/lib/vmware-lookupsvc/conf/server.xml
```

Remove all <Realm> nodes.

Restart the service with the following command:

```
# vmon-cli --restart lookupsvc
```

Additional Information:

CCI-000381 Configure the system to provide only organization-defined mission essential capabilities.

- NIST SP 800-53::CM-7
- NIST SP 800-53A::CM-7.1 (ii)
- NIST SP 800-53 Revision 4::CM-7 a
- NIST SP 800-53 Revision 5::CM-7 a

1.11 VCLU-70-000011 (Manual)

Profile Applicability:

- SEVERITY: CAT II

Description:

Lookup Service must be configured to limit access to internal packages.

```
GROUP ID: V-256716  
RULE ID: SV-256716r888739
```

Rationale:

The "package.access" entry in the "catalina.properties" file implements access control at the package level. When properly configured, a Security Exception will be reported if an errant or malicious webapp attempts to access the listed internal classes directly or if a new class is defined under the protected packages.

The Lookup Service comes preconfigured with the appropriate packages defined in "package.access", and this configuration must be maintained.

Audit:

At the command prompt, run the following command:

```
# grep "package.access" /usr/lib/vmware-lookupsvc/conf/catalina.properties
```

Expected result:

package.access=sun.,org.apache.catalina.,org.apache.coyote.,org.apache.tomcat.,org.apache.jasper.

If the output of the command does not match the expected result, this is a finding.

Remediation:

Navigate to and open:

/usr/lib/vmware-ss0/vmware-sts/conf/catalina.properties

Ensure the "package.access" line is configured as follows:

package.access=sun.,org.apache.catalina.,org.apache.coyote.,org.apache.tomcat.,org.apache.jasper.

Restart the service with the following command:

```
# vmon-cli --restart lookupsvc
```

Additional Information:

CCI-000381 Configure the system to provide only organization-defined mission essential capabilities.

- NIST SP 800-53::CM-7
- NIST SP 800-53A::CM-7.1 (ii)
- NIST SP 800-53 Revision 4::CM-7 a
- NIST SP 800-53 Revision 5::CM-7 a

1.12 VCLU-70-000012 (Manual)

Profile Applicability:

- SEVERITY: CAT II

Description:

Lookup Service must have Multipurpose Internet Mail Extensions (MIMEs) that invoke operating system shell programs disabled.

```
GROUP ID: V-256717  
RULE ID: SV-256717r888742
```

Rationale:

MIME mappings tell the Lookup Service what type of program various file types and extensions are and what external utilities or programs are needed to execute the file type. By ensuring that various shell script MIME types are not included in "web.xml", the server is protected against malicious users tricking the server into executing shell command files.

Audit:

At the command prompt, run the following command:

```
# grep -En '(x-csh<)|(x-sh<)|(x-shar<)|(x-ksh<)' /usr/lib/vmware-  
lookupsvc/conf/web.xml
```

If the command produces any output, this is a finding.

Remediation:

Navigate to and open:

/usr/lib/vmware-lookupsvc/conf/web.xml

Remove all of the following nodes lines:

```
<mime-type>application/x-csh</mime-type>
<mime-type>application/x-shar</mime-type>
<mime-type>application/x-sh</mime-type>
<mime-type>application/x-ksh</mime-type>
```

Restart the service with the following command:

```
# vmon-cli --restart lookupsvc
```

Note: Delete the entire mime-mapping node for the target mime-type.

Example:

```
<mime-mapping>
  <extension>sh</extension>
  <mime-type>application/x-sh</mime-type>
</mime-mapping>
```

Additional Information:

CCI-000381 Configure the system to provide only organization-defined mission essential capabilities.

- NIST SP 800-53::CM-7
- NIST SP 800-53A::CM-7.1 (ii)
- NIST SP 800-53 Revision 4::CM-7 a
- NIST SP 800-53 Revision 5::CM-7 a

1.13 VCLU-70-000013 (Manual)

Profile Applicability:

- SEVERITY: CAT II

Description:

Lookup Service must have mappings set for Java servlet pages.

GROUP ID: V-256718
RULE ID: SV-256718r888745

Rationale:

Resource mapping is the process of tying a particular file type to a process in the web server that can serve that type of file to a requesting client and identify which file types are not to be delivered to a client.

By not specifying which files can and cannot be served to a user, the web server could deliver to a user web server configuration files, log files, password files, etc.

Because Tomcat is a Java-based web server, the main file extension used is *.jsp. This check ensures the *.jsp and *.jspx file types has been properly mapped to servlets.

Audit:

At the command prompt, run the following command:

```
# xmllint --format /usr/lib/vmware-lookupsvc/conf/web.xml | sed  
's/xmlns=".*"/g' | xmllint --xpath '/web-app/servlet-mapping/servlet-  
name[text()="jsp"]/parent::servlet-mapping' -
```

Expected result:

```
<servlet-mapping>  
  <servlet-name>jsp</servlet-name>  
  <url-pattern>*.jsp</url-pattern>  
  <url-pattern>*.jspx</url-pattern>  
</servlet-mapping>
```

If the .jsp and .jspx file url-patterns are not configured as in the expected result, this is a finding.

Remediation:

Navigate to and open:

```
/usr/lib/vmware-lookupsvc/conf/web.xml
```

Navigate to and locate the mapping for the JSP servlet. It is the `<servlet-mapping>` node that contains `<servlet-name>jsp</servlet-name>`.

Configure the node to look like the code snippet below:

```
<!-- The mappings for the JSP servlet -->
<servlet-mapping>
  <servlet-name>jsp</servlet-name>
  <url-pattern>*.jsp</url-pattern>
  <url-pattern>*.jspx</url-pattern>
</servlet-mapping>
```

Restart the service with the following command:

```
# vmon-cli --restart lookupsvc
```

Additional Information:

CCI-000381 Configure the system to provide only organization-defined mission essential capabilities.

- NIST SP 800-53::CM-7
- NIST SP 800-53A::CM-7.1 (ii)
- NIST SP 800-53 Revision 4::CM-7 a
- NIST SP 800-53 Revision 5::CM-7 a

1.14 VCLU-70-000014 (Manual)

Profile Applicability:

- SEVERITY: CAT II

Description:

Lookup Service must not have the Web Distributed Authoring (WebDAV) servlet installed.

```
GROUP ID: V-256719
RULE ID: SV-256719r888748
```

Rationale:

WebDAV is an extension to the HTTP protocol that, when developed, was meant to allow users to create, change, and move documents on a server, typically a web server or web share. WebDAV is not widely used and has serious security concerns because it may allow clients to modify unauthorized files on the web server and must therefore be disabled.

Tomcat uses the "org.apache.catalina.servlets.WebdavServlet" servlet to provide WebDAV services. Because the WebDAV service has been found to have an excessive number of vulnerabilities, this servlet must not be installed. Lookup Service does not configure WebDAV by default.

Audit:

At the command prompt, run the following command:

```
# grep -n 'webdav' /usr/lib/vmware-lookupsvc/conf/web.xml
```

If the command produces any output, this is a finding.

Remediation:

Navigate to and open:

```
/usr/lib/vmware-lookupsvc/conf/web.xml
```

Find the `<servlet-name>webdav</servlet-name>` node and remove the entire parent `<servlet>` block.

Find the `<servlet-name>webdav</servlet-name>` node and remove the entire parent `<servlet-mapping>` block.

Restart the service with the following command:

```
# vmon-cli --restart lookupsvc
```

Additional Information:

CCI-000381 Configure the system to provide only organization-defined mission essential capabilities.

- NIST SP 800-53::CM-7
- NIST SP 800-53A::CM-7.1 (ii)
- NIST SP 800-53 Revision 4::CM-7 a
- NIST SP 800-53 Revision 5::CM-7 a

1.15 VCLU-70-000015 (Manual)

Profile Applicability:

- SEVERITY: CAT II

Description:

Lookup Service must be configured with memory leak protection.

```
GROUP ID: V-256720
RULE ID: SV-256720r888751
```

Rationale:

The Java Runtime environment can cause a memory leak or lock files under certain conditions. Without memory leak protection, Lookup Service can continue to consume system resources, which will lead to "OutOfMemoryErrors" when reloading web applications.

Memory leaks occur when JRE code uses the context class loader to load a singleton as this will cause a memory leak if a web application class loader happens to be the context class loader at the time. The "JreMemoryLeakPreventionListener" class is designed to initialize these singletons when Tomcat's common class loader is the context class loader. Proper use of JRE memory leak protection will ensure that the hosted application does not consume system resources and cause an unstable environment.

Audit:

At the command prompt, run the following command:

```
# grep JreMemoryLeakPreventionListener /usr/lib/vmware-lookupsvc/conf/server.xml
```

Expected result:

```
<Listener
className="org.apache.catalina.core.JreMemoryLeakPreventionListener"/>
```

If the output of the command does not match the expected result, this is a finding.

Remediation:

Navigate to and open:

/usr/lib/vmware-lookupsvc/conf/server.xml

Navigate to the <Server> node.

Add '<Listener
className="org.apache.catalina.core.JreMemoryLeakPreventionListener"/>' to the
<Server> node.

Restart the service with the following command:

```
# vmon-cli --restart lookupsvc
```

Additional Information:

CCI-000381 Configure the system to provide only organization-defined mission essential capabilities.

- NIST SP 800-53::CM-7
- NIST SP 800-53A::CM-7.1 (ii)
- NIST SP 800-53 Revision 4::CM-7 a
- NIST SP 800-53 Revision 5::CM-7 a

1.16 VCLU-70-000016 (Manual)

Profile Applicability:

- SEVERITY: CAT II

Description:

Lookup Service must not have any symbolic links in the web content directory tree.

```
GROUP ID: V-256721
RULE ID: SV-256721r888754
```

Rationale:

A web server is designed to deliver content and execute scripts or applications on the request of a client or user. Containing user requests to files in the directory tree of the hosted web application and limiting the execution of scripts and applications guarantees the user is not accessing information protected outside the application's realm.

By checking that no symbolic links exist in the document root, the web server is protected from users jumping outside the hosted application directory tree and gaining access to the other directories, including the system root.

Audit:

At the command prompt, run the following command:

```
# find /usr/lib/vmware-vsphere-ui/server/static/ -type l -ls
```

If the command produces any output, this is a finding.

Remediation:

At the command prompt, run the following command:

Note: Replace <file_name> for the name of any files that were returned.

```
# unlink <file_name>
```

Repeat the commands for each file that was returned.

Additional Information:

CCI-000381 Configure the system to provide only organization-defined mission essential capabilities.

- NIST SP 800-53::CM-7
- NIST SP 800-53A::CM-7.1 (ii)
- NIST SP 800-53 Revision 4::CM-7 a
- NIST SP 800-53 Revision 5::CM-7 a

1.17 VCLU-70-000017 (Manual)

Profile Applicability:

- SEVERITY: CAT II

Description:

Lookup Service directory tree must have permissions in an out-of-the-box state.

```
GROUP ID: V-256722
RULE ID: SV-256722r888757
```

Rationale:

As a rule, accounts on a web server are to be kept to a minimum. Only administrators, web managers, developers, auditors, and web authors require accounts on the machine hosting the web server. The resources to which these accounts have access must also be closely monitored and controlled. Lookup Service files must be adequately protected with correct permissions as applied out of the box.

Satisfies: SRG-APP-000211-WSR-000030, SRG-APP-000380-WSR-000072

Audit:

At the command prompt, run the following command:

```
# find /usr/lib/vmware-lookupsvc/lib /usr/lib/vmware-lookupsvc/conf -xdev -
type f -a '(' -perm -o+w -o -not -user root -o -not -group root ')' -exec ls
-l {} \;
```

If the command produces any output, this is a finding.

Remediation:

At the command prompt, run the following commands:

```
# chmod o-w <file>
# chown root:root <file>
```

Repeat the command for each file that was returned.

Additional Information:

CCI-001082 Separate user functionality, including user interface services, from system management functionality.

- NIST SP 800-53::SC-2
- NIST SP 800-53A::SC-2.1
- NIST SP 800-53 Revision 4::SC-2
- NIST SP 800-53 Revision 5::SC-2

CCI-001813 Enforce access restrictions using organization-defined mechanisms.

- NIST SP 800-53 Revision 4::CM-5 (1)
- NIST SP 800-53 Revision 5::CM-5 (1) (a)

1.18 VCLU-70-000018 (Manual)

Profile Applicability:

- SEVERITY: CAT II

Description:

Lookup Service must fail to a known safe state if system initialization fails, shutdown fails, or aborts fail.

```
GROUP ID: V-256723
RULE ID: SV-256723r888760
```

Rationale:

Determining a safe state for failure and weighing that against a potential denial of service for users depends on what type of application the web server is hosting. For the Lookup Service, it is preferable that the service abort startup on any initialization failure rather than continuing in a degraded, and potentially insecure, state.

Audit:

At the command line, run the following command:

```
# grep EXIT_ON_INIT_FAILURE /usr/lib/vmware-lookupsvc/conf/catalina.properties
```

Expected result:

org.apache.catalina.startup.EXIT_ON_INIT_FAILURE=true

If the output of the command does not match the expected result, this is a finding.

Remediation:

Navigate to and open:

/usr/lib/vmware-lookupsvc/conf/catalina.properties

Add or change the following line:

org.apache.catalina.startup.EXIT_ON_INIT_FAILURE=true

Restart the service with the following command:

```
# vmon-cli --restart lookupsvc
```

Additional Information:

CCI-001190 Fail to an organization-defined known-system state for the list of organization-defined types of system failures on organization-defined system components on the indicated components while preserving organization-defined system state information in failure.

- NIST SP 800-53::SC-24
- NIST SP 800-53A::SC-24.1 (iv)
- NIST SP 800-53 Revision 4::SC-24
- NIST SP 800-53 Revision 5::SC-24

1.19 VCLU-70-000019 (Manual)

Profile Applicability:

- SEVERITY: CAT II

Description:

Lookup Service must limit the number of allowed connections.

```
GROUP ID: V-256724
RULE ID: SV-256724r888763
```

Rationale:

Limiting the number of established connections is a basic denial-of-service protection and a best practice. Servers where the limit is too high or unlimited could run out of system resources and negatively affect system availability.

Audit:

At the command prompt, run the following command:

```
# xmllint --xpath '/Server/Service/Connector[@port="${bio-
custom.http.port}"]/acceptCount' /usr/lib/vmware-lookupsvc/conf/server.xml
```

Expected result:

```
acceptCount="100"
```

If the output does not match the expected result, this is a finding.

Remediation:

Navigate to and open:

```
/usr/lib/vmware-lookupsvc/conf/server.xml
```

Navigate to the <Connector> configured with port="\${bio-custom.http.port}".

Add or change the following value:

```
acceptCount="100"
```

Restart the service with the following command:

```
# vmon-cli --restart lookupsvc
```

Additional Information:

CCI-001094 Restrict the ability of individuals to launch organization-defined denial of service attacks against other systems.

- NIST SP 800-53::SC-5 (1)
- NIST SP 800-53A::SC-5 (1).1
- NIST SP 800-53 Revision 4::SC-5 (1)
- NIST SP 800-53 Revision 5::SC-5 (1)

1.20 VCLU-70-000020 (Manual)

Profile Applicability:

- SEVERITY: CAT II

Description:

Lookup Service must set URIEncoding to UTF-8.

```
GROUP ID: V-256725
RULE ID: SV-256725r888766
```

Rationale:

Invalid user input occurs when a user inserts data or characters into a hosted application's data entry field and the hosted application is unprepared to process that data. This results in unanticipated application behavior, potentially leading to an application compromise. Invalid user input is one of the primary methods employed when attempting to compromise an application.

An attacker can also enter Unicode characters into hosted applications in an effort to break out of the document home or root home directory or to bypass security checks. Lookup Service must be configured to use a consistent character set via the "URIEncoding" attribute on the Connector nodes.

Audit:

At the command prompt, run the following command:

```
# xmllint --xpath '/Server/Service/Connector[@port="${bio-  
custom.http.port}"]/@URIEncoding' /usr/lib/vmware-lookupsvc/conf/server.xml
```

Expected result:

URIEncoding="UTF-8"

If the output does not match the expected result, this is a finding.

Remediation:

Navigate to and open:

/usr/lib/vmware-lookupsvc/conf/server.xml

Navigate to each of the <Connector> nodes.

Configure each <Connector> node with the value 'URIEncoding="UTF-8"'.

Restart the service with the following command:

```
# vmon-cli --restart lookupsvc
```

Additional Information:

CCI-001310 Checks the validity of organization-defined information inputs to the system.

- NIST SP 800-53::SI-10
- NIST SP 800-53A::SI-10.1
- NIST SP 800-53 Revision 4::SI-10
- NIST SP 800-53 Revision 5::SI-10

1.21 VCLU-70-000021 (Manual)

Profile Applicability:

- SEVERITY: CAT II

Description:

Lookup Service must set the welcome-file node to a default web page.

GROUP ID: V-256726
RULE ID: SV-256726r888769

Rationale:

Enumeration techniques, such as URL parameter manipulation, rely on being able to obtain information about the web server's directory structure by locating directories without default pages. In this scenario, the web server will display to the user a listing of the files in the directory being accessed.

By having a default hosted application web page, the anonymous web user will not obtain directory browsing information or an error message that reveals the server type and version. Ensuring that every document directory has an "index.jsp" (or equivalent) file is one approach to mitigating the vulnerability.

Audit:

At the command prompt, run the following command:

```
# xmllint --format /usr/lib/vmware-lookupsvc/conf/web.xml | sed  
's/xmlns=".*"/g' | xmllint --xpath '/web-app/welcome-file-list' -
```

Expected result:

```
<welcome-file-list>  
  <welcome-file>index.html</welcome-file>  
  <welcome-file>index.htm</welcome-file>  
  <welcome-file>index.jsp</welcome-file>  
</welcome-file-list>
```

If the output of the command does not match the expected result, this is a finding.

Remediation:

Navigate to and open:

/usr/lib/vmware-lookupsvc/conf/web.xml

Add the following section under the **<web-apps>** node:

```
<welcome-file-list>
  <welcome-file>index.html</welcome-file>
  <welcome-file>index.htm</welcome-file>
  <welcome-file>index.jsp</welcome-file>
</welcome-file-list>
```

Restart the service with the following command:

```
# vmon-cli --restart lookupsvc
```

Additional Information:

CCI-001312 Generate error messages that provide information necessary for corrective actions without revealing information that could be exploited.

- NIST SP 800-53::SI-11 b
- NIST SP 800-53A::SI-11.1 (iii)
- NIST SP 800-53 Revision 4::SI-11 a
- NIST SP 800-53 Revision 5::SI-11 a

1.22 VCLU-70-000022 (Manual)

Profile Applicability:

- SEVERITY: CAT II

Description:

The Lookup Service must not show directory listings.

```
GROUP ID: V-256727
RULE ID: SV-256727r888772
```

Rationale:

Enumeration techniques, such as URL parameter manipulation, rely on being able to obtain information about the web server's directory structure by locating directories without default pages. In this scenario, the web server will display to the user a listing of the files in the directory being accessed. Ensuring that directory listing is disabled is one approach to mitigating the vulnerability.

In Tomcat, directory listing is disabled by default but can be enabled via the "listings" parameter. Ensure this node is not present to have the default effect.

Audit:

At the command prompt, run the following command:

```
# xmllint --format /usr/lib/vmware-lookupsvc/conf/web.xml | sed
's/xmlns=".*"/g' | xmllint --xpath '//param-name[text()="listings"]/..' -
```

Expected result:

```
<init-param>
  <param-name>listings</param-name>
  <param-value>false</param-value>
</init-param>
```

If the output of the command does not match the expected result, this is a finding.

Remediation:

Navigate to and open:

/usr/lib/vmware-lookupsvc/conf/web.xml

Set the to "false" in all `<param-name>listing</param-name>` nodes.

The setting should look like the following:

```
<init-param>
  <param-name>listings</param-name>
  <param-value>false</param-value>
</init-param>
```

Restart the service with the following command:

```
# vmon-cli --restart lookupsvc
```

Additional Information:

CCI-001312 Generate error messages that provide information necessary for corrective actions without revealing information that could be exploited.

- NIST SP 800-53::SI-11 b
- NIST SP 800-53A::SI-11.1 (iii)
- NIST SP 800-53 Revision 4::SI-11 a
- NIST SP 800-53 Revision 5::SI-11 a

1.23 VCLU-70-000023 (Manual)

Profile Applicability:

- SEVERITY: CAT II

Description:

Lookup Service must be configured to hide the server version.

```
GROUP ID: V-256728  
RULE ID: SV-256728r888775
```

Rationale:

Web servers will often display error messages to client users, including enough information to aid in the debugging of the error. The information given back in error messages may display the web server type, version, patches installed, plug-ins and modules installed, type of code being used by the hosted application, and any backends being used for data storage.

This information could be used by an attacker to blueprint what type of attacks might be successful. Therefore, Lookup Service must be configured to hide the server version at all times.

Audit:

At the command prompt, run the following command:

```
# xmllint --xpath '/Server/Service/Connector[@port="{bio-custom.http.port}"]/@server' /usr/lib/vmware-lookupsvc/conf/server.xml
```

Expected result:

server="Anonymous"

If the output does not match the expected result, this is a finding.

Remediation:

Navigate to and open:

/usr/lib/vmware-lookupsvc/conf/server.xml

Navigate to each of the <Connector> nodes.

Configure each <Connector> node with 'server="Anonymous"'.

Restart the service with the following command:

```
# vmon-cli --restart lookupsvc
```

Additional Information:

CCI-001312 Generate error messages that provide information necessary for corrective actions without revealing information that could be exploited.

- NIST SP 800-53::SI-11 b
- NIST SP 800-53A::SI-11.1 (iii)
- NIST SP 800-53 Revision 4::SI-11 a
- NIST SP 800-53 Revision 5::SI-11 a

1.24 VCLU-70-000024 (Manual)

Profile Applicability:

- SEVERITY: CAT II

Description:

Lookup Service must be configured to show error pages with minimal information.

```
GROUP ID: V-256729
RULE ID: SV-256729r888778
```

Rationale:

Web servers will often display error messages to client users, including enough information to aid in the debugging of the error. The information given back in error messages may display the web server type, version, patches installed, plug-ins and modules installed, type of code being used by the hosted application, and any backends being used for data storage.

This information could be used by an attacker to blueprint what type of attacks might be successful. Therefore, the Lookup Service must be configured with a catchall error handler that redirects to a standard "error.jsp".

Audit:

At the command prompt, run the following command:

```
# xmllint --xpath
'/Server/Service/Engine/Host/Valve[@className="org.apache.catalina.valves.ErrorReportValve"]' /usr/lib/vmware-lookupsvc/conf/server.xml
```

Expected result:

```
<Valve className="org.apache.catalina.valves.ErrorReportValve"
showServerInfo="false" showReport="false"/>
```

If the output of the command does not match the expected result, this is a finding.

Remediation:

Navigate to and open:

/usr/lib/vmware-lookupsvc/conf/server.xml

Locate the following Host block:

```
<Host ...>
...
</Host>
```

Inside this block, add the following on a new line:

```
<Valve className="org.apache.catalina.valves.ErrorReportValve"
showServerInfo="false" showReport="false"/>
```

Restart the service with the following command:

```
# vmon-cli --restart lookupsvc
```

Additional Information:

CCI-001312 Generate error messages that provide information necessary for corrective actions without revealing information that could be exploited.

- NIST SP 800-53::SI-11 b
- NIST SP 800-53A::SI-11.1 (iii)
- NIST SP 800-53 Revision 4::SI-11 a
- NIST SP 800-53 Revision 5::SI-11 a

1.25 VCLU-70-000025 (Manual)

Profile Applicability:

- SEVERITY: CAT II

Description:

Lookup Service must not enable support for TRACE requests.

```
GROUP ID: V-256730
RULE ID: SV-256730r888781
```

Rationale:

"TRACE" is a technique for a user to request internal information about Tomcat. This is useful during product development but should not be enabled in production. Allowing an attacker to conduct a TRACE operation against the service will expose information that would be useful to perform a more targeted attack. Lookup Service provides the "allowTrace" parameter as means to disable responding to TRACE requests.

Audit:

At the command prompt, run the following command:

```
# grep allowTrace /usr/lib/vmware-lookupsvc/conf/server.xml
```

If "allowTrace" is set to "true", this is a finding.

If no line is returned, this is not a finding.

Remediation:

Navigate to and open:

```
/usr/lib/vmware-lookupsvc/conf/server.xml
```

Locate and navigate to 'allowTrace="true"'.
Remove the 'allowTrace="true"' setting.

Restart the service with the following command:

```
# vmon-cli --restart lookupsvc
```

Additional Information:

CCI-001312 Generate error messages that provide information necessary for corrective actions without revealing information that could be exploited.

- NIST SP 800-53::SI-11 b
- NIST SP 800-53A::SI-11.1 (iii)
- NIST SP 800-53 Revision 4::SI-11 a
- NIST SP 800-53 Revision 5::SI-11 a

1.26 VCLU-70-000026 (Manual)

Profile Applicability:

- SEVERITY: CAT II

Description:

Lookup Service must have the debug option turned off.

```
GROUP ID: V-256731
RULE ID: SV-256731r888784
```

Rationale:

Information needed by an attacker to begin looking for possible vulnerabilities in a web server includes any information about the web server and plug-ins or modules being used. When debugging or trace information is enabled in a production web server, information about the web server, such as web server type, version, patches installed, plug-ins and modules installed, type of code being used by the hosted application, and any backends being used for data storage may be displayed.

Because this information may be placed in logs and general messages during normal operation of the web server, an attacker does not need to cause an error condition to gain this information.

Lookup Service can be configured to set the debugging level. By setting the debugging level to zero (0), no debugging information will be provided to a malicious user.

Audit:

At the command prompt, run the following command:

```
# xmllint --format /usr/lib/vmware-lookupsvc/conf/web.xml | sed
's/xmlns=".*"/g' | xmllint --xpath '//param-name[text()="debug"]/..' -
```

Expected result:

```
<init-param>
  <param-name>debug</param-name>
  <param-value>0</param-value>
</init-param>
```

If the output of the command does not match the expected result, this is a finding.

Remediation:

Navigate to and open:

/usr/lib/vmware-lookupsvc/conf/web.xml

Navigate to all **<debug>** nodes that are not set to "0".

Set the **<param-value>** to "0" in all debug nodes.

Note: The debug setting should look like the following:

```
<init-param>
  <param-name>debug</param-name>
  <param-value>0</param-value>
</init-param>
```

Restart the service with the following command:

```
# vmon-cli --restart lookupsvc
```

Additional Information:

CCI-001312 Generate error messages that provide information necessary for corrective actions without revealing information that could be exploited.

- NIST SP 800-53::SI-11 b
- NIST SP 800-53A::SI-11.1 (iii)
- NIST SP 800-53 Revision 4::SI-11 a
- NIST SP 800-53 Revision 5::SI-11 a

1.27 VCLU-70-000027 (Manual)

Profile Applicability:

- SEVERITY: CAT II

Description:

Lookup Service must use a logging mechanism that is configured to allocate log record storage capacity large enough to accommodate the logging requirements of the web server.

```
GROUP ID: V-256732
RULE ID: SV-256732r888787
```

Rationale:

To ensure the logging mechanism used by the web server has sufficient storage capacity in which to write the logs, the logging mechanism must be able to allocate log record storage capacity. Lookup Service configures log sizes and rotation appropriately as part of its installation routine.

Verifying the logging configuration file (logging.properties) has not been modified is sufficient to determine if the logging configuration has been modified from the default.

Audit:

At the command prompt, run the following command:

```
# rpm -V vmware-lookupsvc | grep logging.properties | grep "^..5....."
```

If the above command returns any output, this is a finding.

Remediation:

Reinstall the vCenter Server Appliance (VCSA) or roll back to a backup. VMware does not support modifying the Lookup Service installation files manually.

Additional Information:

CCI-001849 Allocate audit log storage capacity to accommodate organization-defined audit log retention requirements.

- NIST SP 800-53 Revision 4::AU-4
- NIST SP 800-53 Revision 5::AU-4

1.28 VCLU-70-000028 (Manual)

Profile Applicability:

- SEVERITY: CAT II

Description:

Lookup Service log files must be offloaded to a central log server in real time.

```
GROUP ID: V-256733  
RULE ID: SV-256733r888790
```

Rationale:

Lookup Service produces several logs that must be offloaded from the originating system. This information can then be used for diagnostic, forensics, or other purposes relevant to ensuring the availability and integrity of the hosted application.

Satisfies: SRG-APP-000358-WSR-000163, SRG-APP-000108-WSR-000166, SRG-APP-000125-WSR-000071

Audit:

At the command prompt, run the following command:

```
# rpm -V VMware-visl-integration|grep vmware-services-lookupsvc.conf
```

If the above command returns any output, this is a finding.

Remediation:

Navigate to and open:

/etc/vmware-syslog/vmware-services-lookupsvc.conf

Create the file if it does not exist.

Set the contents of the file as follows:

```
#localhost_access_log
input(type="imfile"
      File="/var/log/vmware/lookupsvc/tomcat/localhost_access.log"
      Tag="lookupsvc-localhost_access"
      Severity="info"
      Facility="local0")
#lookupsvc_stream.log.std
input(type="imfile"
      File="/var/log/vmware/lookupsvc/lookupsvc_stream.log.std*"
      Tag="lookupsvc-std"
      Severity="info"
      Facility="local0")
#lookupserver-default
input(type="imfile"
      File="/var/log/vmware/lookupsvc/lookupserver-default.log"
      Tag="lookupsvc-lookupserver-default"
      Severity="info"
      Facility="local0")
#lookupServer
input(type="imfile"
      File="/var/log/vmware/lookupsvc/lookupServer.log"
      Tag="lookupsvc-lookupServer"
      Severity="info"
      Facility="local0")
#ls-perflogs
input(type="imfile"
      File="/var/log/vmware/lookupsvc/vmware-lookupservice-perf.log"
      Tag="lookupsvc-perf"
      Severity="info"
      Facility="local0")
#ls-gc
input(type="imfile"
      File="/var/log/vmware/lookupsvc/vmware-lookupsvc-gc.log.*.current"
      Tag="lookupsvc-gc"
      Severity="info"
      Facility="local0")
```

Additional Information:

CCI-000139 Alert organization-defined personnel or roles within an organization-defined time period in the event of an audit logging process failure.

- NIST SP 800-53::AU-5 a
- NIST SP 800-53A::AU-5.1 (ii)
- NIST SP 800-53 Revision 4::AU-5 a
- NIST SP 800-53 Revision 5::AU-5 a

CCI-001348 Store audit records on an organization-defined frequency in a repository that is part of a physically different system or system component than the system or component being audited.

- NIST SP 800-53::AU-9 (2)
- NIST SP 800-53A::AU-9 (2).1 (iii)
- NIST SP 800-53 Revision 4::AU-9 (2)
- NIST SP 800-53 Revision 5::AU-9 (2)

CCI-001851 Transfer audit logs per organization-defined frequency to a different system, system component, or media than the system or system component conducting the logging.

- NIST SP 800-53 Revision 4::AU-4 (1)
- NIST SP 800-53 Revision 5::AU-4 (1)

1.29 VCLU-70-000029 (Manual)

Profile Applicability:

- SEVERITY: CAT II

Description:

Lookup Service must be configured with the appropriate ports.

```
GROUP ID: V-256734  
RULE ID: SV-256734r888793
```

Rationale:

Web servers provide numerous processes, features, and functionalities that use TCP/IP ports. Some of these processes may be deemed unnecessary or too unsecure to run on a production system. The ports that Lookup Service listens on are configured in the "catalina.properties" file and must be verified as accurate to their shipping state.

Audit:

At the command prompt, run the following command:

```
# grep '\.port' /usr/lib/vmware-lookupsvc/conf/catalina.properties
```

Expected result:

base.shutdown.port=-1

base.jmx.port=-1

bio-custom.http.port=7090

bio-custom.https.port=8443

If the output of the command does not match the expected result, this is a finding.

Remediation:

Navigate to and open:

/usr/lib/vmware-lookupsvc/conf/catalina.properties

Navigate to the port's specification section.

Set the Lookup Service port specifications according to the shipping configuration below:

base.shutdown.port=-1

base.jmx.port=-1

bio-custom.http.port=7090

bio-custom.https.port=8443

Restart the service with the following command:

```
# vmon-cli --restart lookupsvc
```

Additional Information:

CCI-001762 Disable or remove organization-defined functions, ports, protocols, software, and services within the system deemed to be unnecessary and/or nonsecure.

- NIST SP 800-53 Revision 4::CM-7 (1) (b)
- NIST SP 800-53 Revision 5::CM-7 (1) (b)

1.30 VCLU-70-000030 (Manual)

Profile Applicability:

- SEVERITY: CAT II

Description:

Lookup Service must disable the shutdown port.

```
GROUP ID: V-256735
RULE ID: SV-256735r888796
```

Rationale:

An attacker has at least two reasons to stop a web server. The first is to cause a denial of service, and the second is to put in place changes the attacker made to the web server configuration. If the Tomcat shutdown port feature is enabled, a shutdown signal can be sent to the Lookup Service through this port. To ensure availability, the shutdown port must be disabled.

Audit:

At the command prompt, run the following commands:

```
# xmllint --xpath '/Server/@port' /usr/lib/vmware-lookupsvc/conf/server.xml
```

Expected result:

```
port="{base.shutdown.port}"
```

If the output does not match the expected result, this is a finding.

Remediation:

Navigate to and open:

```
/usr/lib/vmware-lookupsvc/conf/server.xml
```

Ensure the server port is set as follows:

Restart the service with the following command:

```
# vmon-cli --restart lookupsvc
```

Additional Information:

CCI-002385 Protect against or limit the effects of organization-defined types of denial-of-service events.

- NIST SP 800-53 Revision 4::SC-5
- NIST SP 800-53 Revision 5::SC-5 a

1.31 VCLU-70-000031 (Manual)

Profile Applicability:

- SEVERITY: CAT II

Description:

Lookup Service must set the secure flag for cookies.

```
GROUP ID: V-256736  
RULE ID: SV-256736r888799
```

Rationale:

The secure flag is an option that can be set by the application server when sending a new cookie to the user within an HTTP Response. The purpose of the secure flag is to prevent cookies from being observed by unauthorized parties due to the transmission of the cookie in clear text.

By setting the secure flag, the browser will prevent the transmission of a cookie over an unencrypted channel. Lookup Service is configured to only be accessible over a Transport Layer Security (TLS) tunnel, but this cookie flag is still a recommended best practice.

Audit:

At the command prompt, run the following command:

```
# xmllint --format /usr/lib/vmware-lookupsvc/conf/web.xml | sed  
's/xmlns=".*"/g' | xmllint --xpath '/web-app/session-config/cookie-  
config/secure' -
```

Expected result:

```
<secure>true</secure>
```

If the output of the command does not match the expected result, this is a finding.

Remediation:

Navigate to and open:

/usr/lib/vmware-lookupsvc/conf/web.xml

Navigate to the `/<web-apps>/<session-config>/<cookie-config>` node and configure it as follows:

```
<cookie-config>
  <http-only>true</http-only>
  <secure>true</secure>
</cookie-config>
```

Restart the service with the following command:

```
# vmon-cli --restart lookupsvc
```

Additional Information:

CCI-002418 Protect the confidentiality and/or integrity of transmitted information.

- NIST SP 800-53 Revision 4::SC-8
- NIST SP 800-53 Revision 5::SC-8

Appendix: Summary Table

CIS Benchmark Recommendation		Set Correctly	
		Yes	No
1	STIG RULES		
1.1	VCLU-70-000001 (Manual)	☐	☐
1.2	VCLU-70-000002 (Manual)	☐	☐
1.3	VCLU-70-000003 (Manual)	☐	☐
1.4	VCLU-70-000004 (Manual)	☐	☐
1.5	VCLU-70-000005 (Manual)	☐	☐
1.6	VCLU-70-000006 (Manual)	☐	☐
1.7	VCLU-70-000007 (Manual)	☐	☐
1.8	VCLU-70-000008 (Manual)	☐	☐
1.9	VCLU-70-000009 (Manual)	☐	☐
1.10	VCLU-70-000010 (Manual)	☐	☐
1.11	VCLU-70-000011 (Manual)	☐	☐
1.12	VCLU-70-000012 (Manual)	☐	☐
1.13	VCLU-70-000013 (Manual)	☐	☐
1.14	VCLU-70-000014 (Manual)	☐	☐
1.15	VCLU-70-000015 (Manual)	☐	☐
1.16	VCLU-70-000016 (Manual)	☐	☐
1.17	VCLU-70-000017 (Manual)	☐	☐
1.18	VCLU-70-000018 (Manual)	☐	☐
1.19	VCLU-70-000019 (Manual)	☐	☐

CIS Benchmark Recommendation		Set Correctly	
		Yes	No
1.20	VCLU-70-000020 (Manual)	☐	☐
1.21	VCLU-70-000021 (Manual)	☐	☐
1.22	VCLU-70-000022 (Manual)	☐	☐
1.23	VCLU-70-000023 (Manual)	☐	☐
1.24	VCLU-70-000024 (Manual)	☐	☐
1.25	VCLU-70-000025 (Manual)	☐	☐
1.26	VCLU-70-000026 (Manual)	☐	☐
1.27	VCLU-70-000027 (Manual)	☐	☐
1.28	VCLU-70-000028 (Manual)	☐	☐
1.29	VCLU-70-000029 (Manual)	☐	☐
1.30	VCLU-70-000030 (Manual)	☐	☐
1.31	VCLU-70-000031 (Manual)	☐	☐

Appendix: Change History

Date	Version	Changes for this version
Aug 19, 2025	1.0.0	Initial CIS Release